



RTD2473AD/2483AD-CG

Multi-Function Display Controller

Specification

Version 1.00

Last updated: 2011/11/29

1. FEATURES	4
2. ORDERING INFORMATION	6
3. CHIP DATA PATH BLOCK DIAGRAM	7
4. PIN DIAGRAM	8
128 Pin LQFP	8
Table of Pin Assignment	9
MCU GPIO Assignment	14
5. REGISTER DESCRIPTION	15
Global Event Flag	15
Power Control	19
Watch Dog	21
Input Video Capture	22
Input Frame Window	24
FIFO Frequency	27
Scaling Down Control	28
Display Format	32
Display Fine Tune	36
Cyclic-Redundant-Check	37
FIFO Window	38
Scaling Up Function	39
Frame Sync Fine Tune	42
Sync Processor	43
Highlight window	52
Color Processor Control	56
Contrast/Brightness Coefficient	57
Gamma Control	61
Dithering Control(For Display Domain)	63
Overlay/Color Palette/Background Color Control	65
Image Auto Function	66
Dithering Control (For Input Domain)	70
Global Control for LVDS	72
Control for LVDS	81
Test function	85
Embedded OSD	93
Digital Filter	95
Video Color Space Conversion(Input Domain)	97
YUV2RGB	97
Paged Control Register	99
Embedded ADC (Page 0)	100
Embedded LDO(Page 0)	108
ABL(Page 0)	109
LVR(Page 0)	115
Schmitt trigger (Page 0)	116
ADC PLL (Page 1)	117
DISPLAY PLL (Page 1)	125
DCLK Spread Spectrum (Page 1)	126

Multiply PLL for Input Crystal (Page 1)	131
Overall HDMI System Function Block (Page 2)	132
HDCP 1.3 (Page 2)	141
HDMI Video and Audio Part (Page 2).....	148
Power Saving Mode (Page 2).....	183
Internal OSC (Page 6).....	188
Audio DAC (Page 6)	190
Vivid color-DCC (Page 7).....	199
ICM(Page 7).....	206
DCR(Page 7)	209
Pattern Generator in D-Domain (Page 7).....	213
Audio Control (Page 8).....	216
Input Gamma Control (Page 9)	225
GDI PHY(Page B).....	227
TMDS MAC (Page C)	240
MCU register 1(page D)	241
Interrupt Control	248
OSD reorder.....	249
ADC.....	250
DDC.....	254
DDC-CI	257
PWM.....	262
I2C Control Module.....	268
MCU Register2(Page E) SPI-FLASH.....	273
MCU Register2 (Page E) PWM	283
MCU register 3 (page F)	286
GPIO Control.....	286
SFR Access	295
Watchdog Timer.....	298
In System Programming	300
Xdata-SPI-FLASH Write Protect.....	302
Scalar Interface	303
Bank Switch.....	306
Pin Share Register (page 10).....	309
Embedded OSD	325
OSD Compression	377
OSD Special Function	378
6. ELECTRIC SPECIFICATION	395
DC Characteristics.....	395
7. MECHANICAL SPECIFICATION	396

1. Features

General

- Embedded 3 DDC with DDC1/2B/CI
- Zoom scaling up and down
- Embedded one MCU with SPI flash controller.
- It contains 4 ADCs in key pad application
- Require only one crystal to generate all timing.
- Programmable internal low-voltage-reset (LVR)
- High resolution 6 channels PWM output, and wide range selectable PWM frequency.
- Support input format up to FHD.
- Support 27MHz/24MHz/14.318MHz crystal type

Analog RGB Input Interface

- 1 Analog input supported
- Integrated 8-bit triple-channel 210MHz ADC/PLL
- Embedded programmable Schmitt trigger of HSYNC
- Support Sync-On-Green (SOG) and various kinds of composite sync modes
- On-chip high-performance hybrid PLLs
- High resolution true 64 phase ADC PLL
- YPbPr support up to HDTV 1080p resolution

HDMI 1.4a Compliant Digital Input Interface with HDCP

- HDMI Input with embedded high speed switch
- Single link on-chip TMDS receiver up to 225MHz.
- Support long cable
- Adaptive algorithm for TMDS capability
- Data enable only mode support
- High-Bandwidth Digital Content Protection (HDCP 1.3)
- Enhanced protection of HDCP secret key
- Capable of 8-channel I2S/SPDIF output in HDMI application
- ATC Lab certification pass HDMI1.4a compliance test
- Support DVI 1.0

Embedded MCU

- Industrial standard 8051 core with external serial flash
- Low speed ADC for various application
- I2C Master hardware supported

Auto Detection /Auto Calibration

- Input format detection
- Compatibility with standard VESA mode and support user-defined mode
- Smart engine for Phase/Image position/Color calibration

Audio

- 5-band Equalizer
- AVC (Auto Volume Control)
- Output: IIS , SPDIF
- Embedded 2ch Audio DAC
- Embedded headphone amp

Scaling

- Fully programmable zoom ratios
- Independent horizontal/vertical scaling
- Advanced zoom algorithm provides high image quality
- Sharpness/Smooth filter enhancement
- Support non-linear scaling from 4:3 to 16:9 or 16:9 to 4:3

Color Processor

- True 10 bits color processing engine
- xvYCC supported
- sRGB compliance
- Advanced dithering logic for 18-bit panel color depth enhancement
- Dynamic overshoot-smear canceling engine
- Brightness and contrast control
- Programmable 10-bit gamma support
- Peaking/Coring function for video sharpness

VividColor™

- Independent color management (ICM)
- Dynamic contrast control (DCC)
- Precise color mapping (PCM)
- Active adaptive power saving(IAPS)

Output Interface

- Fully programmable display timing generator
- Flexible data pair swapping for easier system design.
- Display clock supports up to 186MHz
- LVDS -output interface on single PCB
- Support 8-bit LVDS output
- Spread-Spectrum DPLL to reduce EMI
- Fixed Last Line output for perfect panel capability

Embedded OSD

- Embedded 20K SRAM dynamically stores OSD command and fonts
- Support multi-color RAM font, 1, 2 and 4-bit per pixel
- 64 color palette
- Maximum 18 window with alpha-blending/gradient / gradient target color / gradient reversed color/ dynamic fade-in/fade-out, bordering/shadow/3D window type



- Rotary 90,180,270 degree
- Independent row shadowing/bordering
- Programmable blinking effects for each character
- OSD-made internal pattern generator for factory mode
- Support 12x18~4x18 proportional font
- Hardware decompression for OSD font
- Support OSD scrolling
- Support 2 independent font based OSD

Power Supply

- 3.3V / 1.2V power supply
- Low standby current (<4mA)