

1	2	3	4	5	6	7																																																							
				FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人																																																							
A							A																																																						
B	LED PIN LED PIN 7.1 3.9 Ø14 6 Max. 1.5 21 M12X0.75 THE SHADED AREA IS ILLUMINATED 0.7 16 Ø8.6 Ø12^{+0.2}₀ PANEL CUTOUT Ø13.1 Ø10.8 0.6 SEAL RING						B																																																						
C	SPECIFICATIONS: 1.SWITCH RATING: 5A/24VDC(DC-12). 2.LAMP CIRCUIT: USING AC/DC LED LAMP,THE TERMINALS NO DIFFERENCE OF ANODE AND CATHODE. 3.MECHANICAL LIFE: ≥1,000,000 cycles(MOMENTARY), ≥500,000 cycles(LATCHING). 4.ELECTRICAL LIFE: ≥50,000 cycles. 5.INITIAL CONTACT RESISTANCE: ≤50mΩ. 6.INSULATION RESISTANCE: ≥1000MΩ(500VDC). 7.POWER-FREQUENCY WITHSTAND VOLTAGE: 1,500V, RMS 50Hz, 1min. 8.OPERATING TEMPERATURE: -25℃~ +55℃(NO FREEZING, KEEP THE AIR FLOWING AROUND PUSHBUTTON). 9.TORQUE: ABOUT 0.3N·m APPLIED TO NUT. 10.OPERATING FORCE: ABOUT 2.5N. 11.OPERATING TRAVEL: ABOUT 2.4mm. 12.FRONT PANEL PROTECTION DEGREE: IP65(IP67 CAN BE CUSTOMIZED); IK07. 13.TERMINAL TYPE: PIN TERMINAL(2X0.5mm). 14.GENERAL TOLERANCE:0-18mm=±0.25, 18-80mm=±0.52. 15.RoHS CAN BE CUSTOMIZED. SCHEMATIC + ○ R □ ○ - DOUBLE-BREAKPOINT SLOW-ACTING CONTACT SWITCH WITH TWO TERMINALS PART NUMBER:ONPOW6312F-10 ■E/J/△/▲/◎/※ <table><tr><td>"■"</td><td>OPERATION MODE</td><td>"▲"</td><td>LAMP VOLTAGE</td><td>"◎"</td><td>CRUST MATERIAL</td></tr><tr><td>NO LETTER</td><td>MOMENTARY</td><td>6V</td><td>AC/DC 6V</td><td>S</td><td>STAINLESS STEEL</td></tr><tr><td>Z</td><td>LATCHING</td><td>12V</td><td>AC/DC 12V</td><td>A</td><td>AL ALLOY(BLACK)</td></tr><tr><td>"△"</td><td>LAMP COLOR</td><td>24V</td><td>AC/DC 24V</td><td>※</td><td>PROTECTION DEGREE</td></tr><tr><td>R</td><td>RED</td><td colspan="2">OTHER VOLTAGE CAN BE MADE TO ORDER</td><td>NO LETTER</td><td>IP65</td></tr><tr><td>G</td><td>GREEN</td><td colspan="2"></td><td>FP</td><td>IP67(CUSTOMIZED)</td></tr><tr><td>Y</td><td>YELLOW</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td>B</td><td>BLUE</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td>W</td><td>WHITE</td><td colspan="2"></td><td colspan="2"></td></tr></table>						"■"	OPERATION MODE	"▲"	LAMP VOLTAGE	"◎"	CRUST MATERIAL	NO LETTER	MOMENTARY	6V	AC/DC 6V	S	STAINLESS STEEL	Z	LATCHING	12V	AC/DC 12V	A	AL ALLOY(BLACK)	"△"	LAMP COLOR	24V	AC/DC 24V	※	PROTECTION DEGREE	R	RED	OTHER VOLTAGE CAN BE MADE TO ORDER		NO LETTER	IP65	G	GREEN			FP	IP67(CUSTOMIZED)	Y	YELLOW					B	BLUE					W	WHITE					C
"■"	OPERATION MODE	"▲"	LAMP VOLTAGE	"◎"	CRUST MATERIAL																																																								
NO LETTER	MOMENTARY	6V	AC/DC 6V	S	STAINLESS STEEL																																																								
Z	LATCHING	12V	AC/DC 12V	A	AL ALLOY(BLACK)																																																								
"△"	LAMP COLOR	24V	AC/DC 24V	※	PROTECTION DEGREE																																																								
R	RED	OTHER VOLTAGE CAN BE MADE TO ORDER		NO LETTER	IP65																																																								
G	GREEN			FP	IP67(CUSTOMIZED)																																																								
Y	YELLOW																																																												
B	BLUE																																																												
W	WHITE																																																												
D							D																																																						
E	BRAND 品牌 红波按钮制造有限公司 ONPOW 欧宝龙® ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. TITLE 名称 ONPOW63 SERIES ANTI-VANDAL PUSH BUTTON DWG NO. 图号 ONPOW6312F-10E(带灯) FILE NAME ONPOW6312F-10E.DWG DRAWN 制图 LJJ 2025/07/05 SCALE 比例 2 : 1 SHEET 张 1/1 UNIT 单位 mm SIZE 图纸 A4 REV. 版本 V1.0						E																																																						
1	2	3	4	5	6	7																																																							